



Lithium electric crawler excavator (0.8-2ton)

性能参数performance parameter	Unit	Specificatin		
型号Model		GKE20	GKE12	GKE08
整车重量Weight	kg	2000	1050	800
标准铲斗容量Bucket capacity	m ³	0.045	0.025	0.02
工作装置形式Working device model		Backhoe		
动力方式 power		lithium battery		
蓄电池电压 battery Voltage	V	72	48	48
蓄电池容量 battery capacity	Ah	230	135	100
理论工作时间 working time	H	>15	>8H	>8H
电机功率motor power	KW	6	4	4
行驶速度(高低速)Travel speed (high and low speed)	km/h	0-6	0-6	0-6
每小时功耗Power consumption per hour		1	1	1
1米内分贝数Decibels within 1 meter	dBA	<60	<60	<60
轮距Track width	mm	820	780	420
履带总长Total length of track	mm	1580	1090	940
平台离地间隙Platform ground clearance	mm	500	380	230
底盘宽度Chassis width	mm	1100	946	720
履带宽度track width	mm	230	180	150
履带材料Track material		Rubber		
总高度overall height	mm	2270	1330	1250
最大地面挖掘半径Maximum ground excavation radius	mm	3700	2400	2050
最大挖掘深度Maximum excavation depth	mm	2150	1650	1200
最大挖掘高度Maximum excavation height	mm	3275	2490	2350
最大卸载高度Maximum unloading height	mm	2385	1750	1600
最大垂直挖机深度Maximum vertical excavator depth	mm	1740	1400	1290
最小回转半径Minimum turning radius	mm	1580	1190	1100
推土铲最大挖地深度Maximum digging depth of bulldozer	mm	180	175	175

